

## Laminated MDF

---

### Section 1. Identification

**Common name:** Laminated MDF

**Grade:** Excel +, Excel, Standard, Natural, Lite, Slotwall, HDF

**Synonym:** MDF panels

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Classification:**

**None**

**Very important:** This product is not dangerous in the form in which it is sent by the manufacturer, but can become dangerous by downstream activities (for example, grinding, sanding, cutting, spraying) which reduce its particle size.

**Signal word:** None

**Hazard statements:**

None

**Precautionary statements:**

None

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	80 - 90
Melamine-Urea-Formaldehyde (mUF)	N/A	8 - 14
Urea	57-13-6	1 - 3
Paraffin waxes	64742-61-6	0.7 - 1.2

---

## Section 4. First aid measures

### Description of first aid if required:

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

#### Eye contact:

Rinse eyes thoroughly with water for at least 15 minutes.

#### Skin contact:

Wash with plenty of water and soap.

#### Inhalation:

Bring the conscious victim to fresh air.

#### Ingestion:

Do NOT induce vomiting.

#### Indication of immediate medical attention and special treatment needed, if necessary:

Treat symptomatically

#### Most important acute symptoms and effects:

No known acute effects and/or symptoms.

#### Most important delayed symptoms and effects:

No known chronic effects and/or symptoms.

---

## Section 5. Firefighting measures

### Flammability of the product:

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

### Flash point:

N/A

### Auto-ignition temperature:

218°C / 424°F - 246°C / 475°F (variable)

### Products of combustion:

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

### Special protective actions for fire-fighters:

Wear self-contained breathing apparatus and appropriate protective clothing.

### Suitable extinguishing media:

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

### Specific hazard arising from the chemical:

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

---

## Section 6. Accidental release measures

Product poses no accidental spill hazards.

### Personal precautions, protective equipment and emergency procedures:

**For non emergency personnel:** Evacuate the area.

**For emergency personnel:** Wear appropriate protective equipment (see section 8)

### Environmental precautions:

Not applicable

### Methods and material for containment and cleaning up:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

---

## Section 7. Handling and storage

### Precautions in Handling:

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

### Precautions in Storage:

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values at which the product will be used.

---

## Section 8. Exposure Controls, Personal Protections

### Control parameters:

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Paraffin waxes	64742-61-6	TWA	2 mg/m <sup>3</sup>	CNESST
		TWA	2 mg/m <sup>3</sup>	ACGIH

### Engineering controls:

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

### Personal protective equipment:

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

## Section 9. Physical and chemical properties

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

## Section 10. Stability and reactivity

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

## Section 11. Toxicological information

### Acute toxicity:

Component	CAS	Value
Urea	57-13-6	DL <sub>50</sub> Oral: Rat = 8471 mg/kg DL <sub>50</sub> Oral: Mouse = 11000 mg/kg
Paraffin waxes	64742-61-6	DL <sub>50</sub> Oral: Rat > 5000 mg/kg DL <sub>50</sub> Cutaneous: Rabbit = 4000 mg/kg

### Skin corrosion/irritation:

Not applicable

### Serious eye damage/irritation:

Not applicable

### Respiratory or skin sensitisation:

Not applicable

### Gem cell mutagenicity:

Not applicable

### Carcinogenicity:

Not applicable

### Reproductive toxicity:

Not applicable

### STOT- Single exposure:

Not applicable

### STOT- repeated exposure:

Not applicable

### Aspiration hazard:

Not applicable

### Information on likely route of exposure:

Not applicable

---

## Section 12. Ecological information

### Ecological data for aquatic environments:

Component	CAS	Value
Urea	57-13-6	CL <sub>50</sub> - <i>Poecilia reticulata</i> (guppy) 17500 mg/L - 96h CE <sub>50</sub> - <i>Daphnia magna</i> 3910 mg/L - 48h

---

**Persistence and degradability:**

Data not available

**Bioaccumulative potential:**

Data not available

**Mobility in soil:**

Data not available

**Other adverse effects:**

Data not available

---

**Section 13. Disposal considerations**

**Waste disposal:**

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

**Section 14. Transportation information**

No TDG/DOT/IMDG/IATA Classification

---

**Section 15. Regulatory information**

**NFPA Classification:**



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

**U.S. Federal regulations**

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

**Date of issue:**

2020-11-24

**Version:**

2.1

**Elaborated by:**

Toxyscan inc.

**Notice to reader:**

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Références:**

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*

## MDF

---

### Section 1. Identification

**Common name:** MDF

**Grade:** Excel +, Excel, Standard, Natural, Lite, Slotwall, HDF

**Synonym:** MDF panels

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Classification:**

**None**

**Very important:** This product is not dangerous in the form in which it is sent by the manufacturer, but can become dangerous by downstream activities (for example, grinding, sanding, cutting, spraying) which reduce its particle size.

**Signal word:** None

**Hazard statements:**

None

**Precautionary statements:**

None

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	80 - 90
Melamine-Urea-Formaldehyde (mUF)	N/A	8 - 14
Urea	57-13-6	1 - 3
Paraffin waxes	64742-61-6	0.7 - 1.2

---

## Section 4. First aid measures

### Description of first aid if required:

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

### Eye contact:

Rinse eyes thoroughly with water for at least 15 minutes.

### Skin contact:

Wash with plenty of water and soap.

### Inhalation:

Bring the conscious victim to fresh air.

### Ingestion:

Do NOT induce vomiting.

### Indication of immediate medical attention and special treatment needed, if necessary:

Treat symptomatically

### Most important acute symptoms and effects:

No known acute effects and/or symptoms.

### Most important delayed symptoms and effects:

No known chronic effects and/or symptoms.

---

## Section 5. Firefighting measures

### Flammability of the product:

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

### Flash point:

N/A

### Auto-ignition temperature:

218°C / 424°F - 246°C / 475°F (variable)

### Products of combustion:

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

### Special protective actions for fire-fighters:

Wear self-contained breathing apparatus and appropriate protective clothing.

### Suitable extinguishing media:

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

### Specific hazard arising from the chemical:

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

---

## Section 6. Accidental release measures

Product poses no accidental spill hazards.

### Personal precautions, protective equipment and emergency procedures:

**For non emergency personnel:** Evacuate the area.

**For emergency personnel:** Wear appropriate protective equipment (see section 8)

### Environmental precautions:

Not applicable

### Methods and material for containment and cleaning up:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.



---

## Section 7. Handling and storage

### Precautions in Handling:

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

### Precautions in Storage:

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values at which the product will be used.

---

## Section 8. Exposure Controls, Personal Protections

### Control parameters:

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Paraffin waxes	64742-61-6	TWA	2 mg/m <sup>3</sup>	CNESST
		TWA	2 mg/m <sup>3</sup>	ACGIH

### Engineering controls:

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

### Personal protective equipment:

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

## Section 9. Physical and chemical properties

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

## Section 10. Stability and reactivity

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

## Section 11. Toxicological information

### Acute toxicity:

Component	CAS	Value
Urea	57-13-6	DL <sub>50</sub> Oral: Rat = 8471 mg/kg DL <sub>50</sub> Oral: Mouse = 11000 mg/kg
Paraffin waxes	64742-61-6	DL <sub>50</sub> Oral: Rat > 5000 mg/kg DL <sub>50</sub> Cutaneous: Rabbit = 4000 mg/kg

### Skin corrosion/irritation:

Not applicable

### Serious eye damage/irritation:

Not applicable

### Respiratory or skin sensitisation:

Not applicable

### Gem cell mutagenicity:

Not applicable

### Carcinogenicity:

Not applicable

### Reproductive toxicity:

Not applicable

### STOT- Single exposure:

Not applicable

### STOT- repeated exposure:

Not applicable

### Aspiration hazard:

Not applicable

### Information on likely route of exposure:

Not applicable

---

## Section 12. Ecological information

### Ecological data for aquatic environments:

Component	CAS	Value
Urea	57-13-6	CL <sub>50</sub> - <i>Poecilia reticulata</i> (guppy) 17500 mg/L - 96h CE <sub>50</sub> - <i>Daphnia magna</i> 3910 mg/L - 48h

---

**Persistence and degradability:**

Data not available

**Bioaccumulative potential:**

Data not available

**Mobility in soil:**

Data not available

**Other adverse effects:**

Data not available

---

**Section 13. Disposal considerations**

**Waste disposal:**

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

**Section 14. Transportation information**

No TDG/DOT/IMDG/IATA Classification

---

**Section 15. Regulatory information**

**NFPA Classification:**



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

**U.S. Federal regulations**

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

**Date of issue:**

2020-11-24

**Version:**

2.1

**Elaborated by:**

Toxyscan inc.

**Notice to reader:**

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

**Références:**

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*

## Fire retardant NuGreen MDF

---

### Section 1. Identification

**Common name:** Fire retardant NuGreen MDF

**Grade:** N/A

**Synonym:** MDF panels

**Material uses:** Construction material

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Very important:** This product is not dangerous in the form in which it is shipped by the manufacturer, but can become dangerous through downstream activities (for example, grinding, sanding, cutting, spraying) that reduce its particle size. These hazards are described below.

The classifications below are based on wood dust and the polymer component.

**Classification:**



Combustible dust

Respiratory sensitization, Category 1

Skin sensitization, Category 1

Carcinogenicity, Category 2

Specific target organ toxicity - Repeated exposure, Category 2

**Signal word:** Danger

**Hazard statements:**

H317: May cause an allergic skin reaction.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements:**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: Wear respiratory protection.

P302+P352: IF ON SKIN: Wash with plenty of water and soap.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314: Get medical advice/attention if you feel unwell.

P321: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

P501: Dispose of contents / container by a local waste disposal company according to regional regulations.

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	76 - 83
Siriono N5000	N/A	14 - 18
Methylene diphenyl 4,4'-diisocyanate	101-68-8	2 - 5
Paraffin waxes	64742-61-6	0.7 - 1.2

---

### Section 4. First aid measures

#### Description of first aid if required:

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

#### Eye contact:

Rinse eyes thoroughly with water for at least 15 minutes.

#### Skin contact:

Wash with plenty of water and soap.

#### Inhalation:

Bring the conscious victim to fresh air.

#### Ingestion:

Do NOT induce vomiting.

#### Indication of immediate medical attention and special treatment needed, if necessary:

Treat symptomatically

#### Most important acute symptoms and effects:

No known acute effects and/or symptoms.

#### Most important delayed symptoms and effects:

May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

---

### Section 5. Firefighting measures

#### Flammability of the product:

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

#### Flash point:

N/A

**Auto-ignition temperature:**

218°C / 424°F - 246°C / 475°F (variable)

**Products of combustion:**

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

**Special protective actions for fire-fighters:**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media:**

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

**Specific hazard arising from the chemical:**

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

**Section 6. Accidental release measures**

Product poses no accidental spill hazards.

**Personal precautions, protective equipment and emergency procedures:****For non emergency personnel:** Evacuate the area.**For emergency personnel:** Wear appropriate protective equipment (see section 8)**Environmental precautions:**

Not applicable

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

**Section 7. Handling and storage****Precautions in Handling:**

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values at which the product will be used.

**Section 8. Exposure Controls, Personal Protections****Control parameters:**

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Methylene diphenyl 4,4'-diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
Paraffin waxes	64742-61-6	TWA	2 mg/m <sup>3</sup>	CNESST
		TWA	2 mg/m <sup>3</sup>	ACGIH

**Engineering controls:**

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

**Personal protective equipment:**

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

**Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

**Section 10. Stability and reactivity**

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

**Section 11. Toxicological information****Acute toxicity:**

Component	CAS	Value
Methylene diphenyl 4,4'-diisocyanate	101-68-8	DL <sub>50</sub> Oral: Rat = 9200 mg/kg CL <sub>50</sub> Inhalation: Rat = 2.24 mg/L 1h
Paraffin waxes	64742-61-6	DL <sub>50</sub> Oral: Rat > 5000 mg/kg DL <sub>50</sub> Cutaneous: Rabbit = 4000 mg/kg



**Skin corrosion/irritation:**

Methylene diphenyl 4,4'-diisocyanate: Causes skin irritation

**Serious eye damage/irritation:**

Methylene diphenyl 4,4'-diisocyanate: Causes serious eye irritation

**Respiratory or skin sensitisation:**

Methylene diphenyl 4,4'-diisocyanate: May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled

**Gem cell mutagenicity:**

Not applicable

**Carcinogenicity:**

Methylene diphenyl 4,4'-diisocyanate: Suspected of causing cancer

**Reproductive toxicity:**

Not applicable

**STOT- Single exposure:**

Methylene diphenyl 4,4'-diisocyanate: May cause respiratory irritation

**STOT- repeated exposure:**

Methylene diphenyl 4,4'-diisocyanate: May cause damage to organs through prolonged or repeated exposure (respiratory system)

**Aspiration hazard:**

Not applicable

**Information on likely route of exposure:**

Not applicable

---

**Section 12. Ecological information****Ecological data for aquatic environments:**

Component	CAS	Value
Methylene diphenyl 4,4'-diisocyanate	101-68-8	CE <sub>50</sub> - Daphnia magna 0.35 mg/L - 24h

**Persistence and degradability:**

Data not available

**Bioaccumulative potential:**

Data not available

**Mobility in soil:**

Data not available

**Other adverse effects:**

Data not available

---

**Section 13. Disposal considerations****Waste disposal:**

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

**Section 14. Transportation information**

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### NFPA Classification:



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

### Date of issue:

2020-05-13

### Version:

2.1

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*

## Laminated raw particle board

---

### Section 1. Identification

**Common name:** Laminated raw particle board

**Grade:** M0, M1, MS, M2, M3i, LD1, LD2

**Synonym:** Particle

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Classification:**

**None**

**Very important:** This product is not dangerous in the form in which it is sent by the manufacturer, but can become dangerous by downstream activities (for example, grinding, sanding, cutting, spraying) which reduce its particle size.

**Signal word:** None

**Hazard statements:**

None

**Precautionary statements:**

None

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	80 - 90
Melamine-Urea-Formaldehyde	N/A	6 - 9

---

### Section 4. First aid measures

**Description of first aid if required:**

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

**Eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes.

**Skin contact:**

Wash with plenty of water and soap.

**Inhalation:**

Bring the conscious victim to fresh air.

**Ingestion:**

Do NOT induce vomiting.

**Indication of immediate medical attention and special treatment needed, if necessary:**

Treat symptomatically

**Most important acute symptoms and effects:**

No known acute effects and/or symptoms.

**Most important delayed symptoms and effects:**

No known chronic effects and/or symptoms.

---

**Section 5. Firefighting measures****Flammability of the product:**

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

**Flash point:**

N/A

**Auto-ignition temperature:**

218°C / 424°F - 246°C / 475°F (variable)

**Products of combustion:**

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

**Special protective actions for fire-fighters:**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media:**

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

**Specific hazard arising from the chemical:**

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

---

**Section 6. Accidental release measures**

Product poses no accidental spill hazards.

**Personal precautions, protective equipment and emergency procedures:**

**For non emergency personnel:** Evacuate the area.

**For emergency personnel:** Wear appropriate protective equipment (see section 8)

**Environmental precautions:**

Not applicable

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

---

**Section 7. Handling and storage****Precautions in Handling:**

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values ??at which the product will be used.

---

**Section 8. Exposure Controls, Personal Protections**
**Control parameters:**

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Formaldehyde	50-00-0	Ceiling	3 mg/m <sup>3</sup>	CNESST
		STEL	2 ppm	OSHA
		TWA	0.75 ppm	OSHA
		Ceiling	0.3 ppm	ACGIH

**Engineering controls:**

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

**Personal protective equipment:**

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

**Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

## Section 10. Stability and reactivity

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

## Section 11. Toxicological information

### Acute toxicity:

Component	CAS	Value
Formaldehyde	50-00-0	CL <sub>50</sub> Inhalation: Rat - = 177 ppm 4h

### Skin corrosion/irritation:

Formaldehyde: May cause skin irritation

### Serious eye damage/irritation:

Formaldehyde: Causes serious eye irritation

### Respiratory or skin sensitisation:

Not applicable

### Gem cell mutagenicity:

Formaldehyde: Suspected of causing genetic defects

### Carcinogenicity:

Formaldehyde: May cause cancer

### Reproductive toxicity:

Not applicable

### STOT- Single exposure:

Formaldehyde: May cause respiratory irritation

### STOT- repeated exposure:

Not applicable

### Aspiration hazard:

Not applicable

### Information on likely route of exposure:

Not applicable

---

## Section 12. Ecological information

### Ecological data for aquatic environments:

None

### Persistence and degradability:

Data not available

### Bioaccumulative potential:

Data not available

### Mobility in soil:

Data not available

### Other adverse effects:

Data not available

---

---

## Section 13. Disposal considerations

### Waste disposal:

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

## Section 14. Transportation information

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### NFPA Classification:



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

### Date of issue:

2020-05-13

### Version:

2.1

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*

## Laminated raw particle board

---

### Section 1. Identification

**Common name:** Laminated raw particle board

**Grade:** M0, M1, MS, M2, M3i, LD1, LD2

**Synonym:** Particle

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Classification:**

**None**

**Very important:** This product is not dangerous in the form in which it is sent by the manufacturer, but can become dangerous by downstream activities (for example, grinding, sanding, cutting, spraying) which reduce its particle size.

**Signal word:** None

**Hazard statements:**

None

**Precautionary statements:**

None

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	80 - 90
Melamine-Urea-Formaldehyde	N/A	6 - 9

---

### Section 4. First aid measures

**Description of first aid if required:**

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:



**Eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes.

**Skin contact:**

Wash with plenty of water and soap.

**Inhalation:**

Bring the conscious victim to fresh air.

**Ingestion:**

Do NOT induce vomiting.

**Indication of immediate medical attention and special treatment needed, if necessary:**

Treat symptomatically

**Most important acute symptoms and effects:**

No known acute effects and/or symptoms.

**Most important delayed symptoms and effects:**

No known chronic effects and/or symptoms.

---

**Section 5. Firefighting measures****Flammability of the product:**

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

**Flash point:**

N/A

**Auto-ignition temperature:**

218°C / 424°F - 246°C / 475°F (variable)

**Products of combustion:**

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

**Special protective actions for fire-fighters:**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media:**

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

**Specific hazard arising from the chemical:**

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

---

**Section 6. Accidental release measures**

Product poses no accidental spill hazards.

**Personal precautions, protective equipment and emergency procedures:**

**For non emergency personnel:** Evacuate the area.

**For emergency personnel:** Wear appropriate protective equipment (see section 8)

**Environmental precautions:**

Not applicable

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

---

**Section 7. Handling and storage****Precautions in Handling:**

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values ??at which the product will be used.

---

**Section 8. Exposure Controls, Personal Protections**
**Control parameters:**

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Formaldehyde	50-00-0	Ceiling	3 mg/m <sup>3</sup>	CNESST
		STEL	2 ppm	OSHA
		TWA	0.75 ppm	OSHA
		Ceiling	0.3 ppm	ACGIH

**Engineering controls:**

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

**Personal protective equipment:**

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

**Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

## Section 10. Stability and reactivity

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

## Section 11. Toxicological information

### Acute toxicity:

Component	CAS	Value
Formaldehyde	50-00-0	CL <sub>50</sub> Inhalation: Rat - = 177 ppm 4h

### Skin corrosion/irritation:

Formaldehyde: May cause skin irritation

### Serious eye damage/irritation:

Formaldehyde: Causes serious eye irritation

### Respiratory or skin sensitisation:

Not applicable

### Gem cell mutagenicity:

Formaldehyde: Suspected of causing genetic defects

### Carcinogenicity:

Formaldehyde: May cause cancer

### Reproductive toxicity:

Not applicable

### STOT- Single exposure:

Formaldehyde: May cause respiratory irritation

### STOT- repeated exposure:

Not applicable

### Aspiration hazard:

Not applicable

### Information on likely route of exposure:

Not applicable

---

## Section 12. Ecological information

### Ecological data for aquatic environments:

None

### Persistence and degradability:

Data not available

### Bioaccumulative potential:

Data not available

### Mobility in soil:

Data not available

### Other adverse effects:

Data not available

---

---

## Section 13. Disposal considerations

### Waste disposal:

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

## Section 14. Transportation information

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### NFPA Classification:



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

### Date of issue:

2020-05-13

### Version:

2.1

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*

## NuGreen MDF

---

### Section 1. Identification

**Common name:** NuGreen MDF

**Grade:** NuGreen MR50, NuGreen 0

**Synonym:** MDF panels

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Very important: This product is not dangerous in the form in which it is shipped by the manufacturer, but can become dangerous through downstream activities (for example, grinding, sanding, cutting, spraying) that reduce its particle size. These hazards are described below.**

The classifications below are based on wood dust and the polymer component.

**Classification:**



Combustible dust

Respiratory sensitization, Category 1

Skin sensitization, Category 1

Carcinogenicity, Category 2

Specific target organ toxicity - Repeated exposure, Category 2

**Signal word:** Danger

**Hazard statements:**

H317: May cause an allergic skin reaction.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements:**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P284: Wear respiratory protection.  
P302+P352: IF ON SKIN: Wash with plenty of water and soap.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P314: Get medical advice/attention if you feel unwell.  
P321: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.  
P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.  
P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor.  
P501: Dispose of contents / container by a local waste disposal company according to regional regulations.

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	85 - 94
Methylene diphenyl 4,4'-diisocyanate	101-68-8	2 - 5
Paraffin waxes	64742-61-6	0.7 - 1.2
Urea	57-13-6	0.3 - 0.8

---

### Section 4. First aid measures

#### Description of first aid if required:

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

#### Eye contact:

Rinse eyes thoroughly with water for at least 15 minutes.

#### Skin contact:

Wash with plenty of water and soap.

#### Inhalation:

Bring the conscious victim to fresh air.

#### Ingestion:

Do NOT induce vomiting.

#### Indication of immediate medical attention and special treatment needed, if necessary:

Treat symptomatically

#### Most important acute symptoms and effects:

No known acute effects and/or symptoms.

#### Most important delayed symptoms and effects:

May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

---

### Section 5. Firefighting measures

#### Flammability of the product:

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

#### Flash point:

N/A

**Auto-ignition temperature:**

218°C / 424°F - 246°C / 475°F (variable)

**Products of combustion:**

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

**Special protective actions for fire-fighters:**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media:**

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

**Specific hazard arising from the chemical:**

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

**Section 6. Accidental release measures**

Product poses no accidental spill hazards.

**Personal precautions, protective equipment and emergency procedures:****For non emergency personnel:** Evacuate the area.**For emergency personnel:** Wear appropriate protective equipment (see section 8)**Environmental precautions:**

Not applicable

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

**Section 7. Handling and storage****Precautions in Handling:**

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values at which the product will be used.

**Section 8. Exposure Controls, Personal Protections****Control parameters:**

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Methylene diphenyl 4,4'-diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
Paraffin waxes	64742-61-6	TWA	2 mg/m <sup>3</sup>	CNESST
		TWA	2 mg/m <sup>3</sup>	ACGIH

**Engineering controls:**

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

**Personal protective equipment:**

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

**Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

**Section 10. Stability and reactivity**

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

**Section 11. Toxicological information****Acute toxicity:**

Component	CAS	Value
Methylene diphenyl 4,4'-diisocyanate	101-68-8	DL <sub>50</sub> Oral: Rat = 9200 mg/kg CL <sub>50</sub> Inhalation: Rat = 2.24 mg/L 1h
Paraffin waxes	64742-61-6	DL <sub>50</sub> Oral: Rat > 5000 mg/kg DL <sub>50</sub> Cutaneous: Rabbit = 4000 mg/kg
Urea	57-13-6	DL <sub>50</sub> Oral: Rat = 8471 mg/kg DL <sub>50</sub> Oral: Mouse = 11000 mg/kg



**Skin corrosion/irritation:**

Methylene diphenyl 4,4'-diisocyanate: Causes skin irritation

**Serious eye damage/irritation:**

Methylene diphenyl 4,4'-diisocyanate: Causes serious eye irritation

**Respiratory or skin sensitisation:**

Methylene diphenyl 4,4'-diisocyanate: May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled

**Gem cell mutagenicity:**

Not applicable

**Carcinogenicity:**

Methylene diphenyl 4,4'-diisocyanate: Suspected of causing cancer

**Reproductive toxicity:**

Not applicable

**STOT- Single exposure:**

Methylene diphenyl 4,4'-diisocyanate: May cause respiratory irritation

**STOT- repeated exposure:**

Methylene diphenyl 4,4'-diisocyanate: May cause damage to organs through prolonged or repeated exposure (respiratory system)

**Aspiration hazard:**

Not applicable

**Information on likely route of exposure:**

Not applicable

---

**Section 12. Ecological information****Ecological data for aquatic environments:**

Component	CAS	Value
Methylene diphenyl 4,4'-diisocyanate	101-68-8	CE <sub>50</sub> - Daphnia magna 0.35 mg/L - 24h
Urea	57-13-6	CL <sub>50</sub> - Poecilia reticulata (guppy) 17500 mg/L - 96h CE <sub>50</sub> - Daphnia magna 3910 mg/L - 48h

**Persistence and degradability:**

Data not available

**Bioaccumulative potential:**

Data not available

**Mobility in soil:**

Data not available

**Other adverse effects:**

Data not available

---

**Section 13. Disposal considerations****Waste disposal:**

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

## Section 14. Transportation information

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### NFPA Classification:



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

### Date of issue:

2020-05-13

### Version:

2.1

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*

## Nexos Exterior Panel

---

### Section 1. Identification

**Common name:** Nexos Exterior Panel

**Synonym:** Exterior grade panel

**Material uses:** Exterior millwork, mouldings and signs.

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

**Or call your local Emergency Health Services Center.**

---

### Section 2. Hazards identifications

**Note:** This product is not hazardous in the form in which it is shipped by the manufacturer but may become hazardous by downstream activities (e.g., grinding, sanding, cutting, pulverizing) that reduce its particle size. Those hazards are described below.

**Classification:**



Combustible dust

Skin sensitization, Category 1

Carcinogenicity, Category 2

Specific target organ toxicity - Repeated exposure, Category 2

**Signal word:** Warning

**Hazard statements:**

H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements:**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water and soap.

P314: Get medical advice/attention if you feel unwell.

P321: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P501: Dispose of contents / container by a local waste disposal company according to regional regulations.

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	80 - 90
Methylene diphenyl 4,4'-diisocyanate	101-68-8	2 - 5
Urea	57-13-6	0.7 - 1.2
Paraffin waxes	64742-61-6	1.2 - 3

---

### Section 4. First aid measures

#### Description of first aid if required:

First aid advice does not apply to the form shipped by the manufacturer. The advice applies following the production of wood dust created by cutting or sanding activities.

#### Eye contact:

Rinse eyes thoroughly with water for at least 15 minutes.

#### Skin contact:

Wash with plenty of water and soap.

#### Inhalation:

Bring the conscious victim to fresh air.

#### Ingestion:

Do not induce vomiting. If large amounts were swallowed, give water.

#### Indication of immediate medical attention and special treatment needed, if necessary:

Treat according to symptoms.

#### Most important acute symptoms and effects:

No known acute effects and/or symptoms.

#### Most important delayed symptoms and effects:

May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

---

### Section 5. Fire fighting measures

#### Flammability of the product:

Combustible. Wood dusts are combustible and may form an explosive mix with air in the right circumstances and concentrations.

#### Flash point:

N/A

#### Auto-ignition temperature:

N/A

#### Products of combustion:

Carbon oxides

#### Special protective actions for fire-fighters:

Wear self-contained breathing apparatus and appropriate protective clothing.

#### Suitable extinguishing media:

Use means of extinction the most suited to the surrounding materials.

Treat as wood fire.

---

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

**For non emergency personnel:** Evacuate the area.

**For emergency personnel:** Wear appropriate protective equipment (see section 8).

### Environmental precautions:

Not applicable

### Methods and material for containment and cleaning up:

Use appropriate tools to put the spilled solid in a convenient waste disposal container. In particular a broom or a vacuum cleaner for wood dust.

---

## Section 7. Handling and storage

### Precautions in Handling:

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

### Precautions in Storage:

Keep container tightly closed in a cool, dry and well-ventilated place.

---

## Section 8. Exposure Controls, Personal Protections

### Control parameters:

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Methylene diphenyl 4,4'-diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
Paraffin waxes	64742-61-6	TWA	2 mg/m <sup>3</sup>	CNESST
		TWA	2 mg/m <sup>3</sup>	ACGIH

### Engineering controls:

Use mechanical exhaust or laboratory fumehood to avoid exposure.

### Personal protective equipment:

**Eyes:** Wear safety glasses.

**Skin/body:** Wear suitable protective clothing.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear resistant protective gloves.

**Other:** Provide an emergency eye wash in the immediate work area.

---

## Section 9. Physical and chemical properties

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood odour

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Wood

**Flash point:** Data not available

**Auto-ignition temperature:** Data not available

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

## Section 10. Stability and reactivity

**Chemical stability:** Stable under recommended storage conditions.

**Conditions to avoid:** High temperatures, humidities, incompatible materials. Avoid open flames and generation of dust.

**Incompatible materials:** Strong acids, strong bases, strong oxidizing agents

**Hazardous decomposition products:** Carbon oxides

---

## Section 11. Toxicological information

**Acute toxicity:**

Component	CAS	Value
Methylene diphenyl 4,4'-diisocyanate	101-68-8	DL <sub>50</sub> Oral: Rat = 9200 mg/kg CL <sub>50</sub> Inhalation: Rat - = 2.24 mg/L 1h
Urea	57-13-6	DL <sub>50</sub> Oral: Rat = 8471 mg/kg DL <sub>50</sub> Oral: Mouse = 11000 mg/kg
Paraffin waxes	64742-61-6	DL <sub>50</sub> Oral: Rat > 5000 mg/kg DL <sub>50</sub> Cutaneous: Rabbit = 4000 mg/kg

**Skin corrosion/irritation:**

Methylene diphenyl 4,4'-diisocyanate: Causes skin irritation

**Serious eye damage/irritation:**

Methylene diphenyl 4,4'-diisocyanate: Causes serious eye irritation

**Respiratory or skin sensitisation:**

Methylene diphenyl 4,4'-diisocyanate: May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled

**Gem cell mutagenicity:**

Not applicable

**Carcinogenicity:**

Methylene diphenyl 4,4'-diisocyanate: Suspected of causing cancer

**Reproductive toxicity:**

Not applicable

**STOT- Single exposure:**

Methylene diphenyl 4,4'-diisocyanate: May cause respiratory irritation.

**STOT- repeated exposure:**

Methylene diphenyl 4,4'-diisocyanate: May cause damage to organs through prolonged or repeated exposure (respiratory system).

**Aspiration hazard:**

Not applicable

**Information on likely route of exposure:**

Not applicable

---

**Section 12. Ecological information****Ecological data for aquatic environments:**

Component	CAS	Value
Methylene diphenyl 4,4'-diisocyanate	101-68-8	CE <sub>50</sub> - Daphnia magna 0.35 mg/L - 24h
Urea	57-13-6	CL <sub>50</sub> - Poecilia reticulata (guppy) 17500 mg/L - 96h CE <sub>50</sub> - Daphnia magna 3910 mg/L - 48h

**Persistence and degradability:**

Data not available

**Bioaccumulative potential:**

Data not available

**Mobility in soil:**

Data not available

**Other adverse effects:**

Data not available

---

**Section 13. Disposal considerations****Waste disposal:**

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

**Section 14. Transportation information**

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### General product information:

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the safety data sheet contains all of the required information.

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

**Occupational Safety and Health Administration:** Wood products are not considered dangerous merchandise according to mentioned criteria in the Hazard Communication Standard of OSHA 29 CFR 1910.1200. However, diisocyanate and wood dusts produced by sawing, sanding or shaping of the panels may be hazardous.

---

## Section 16. Additional information

### Date of issue:

2020-05-13

### Version:

3.1

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - united nations*



## NuGreen 2 Laminated raw particle board

---

### Section 1. Identification

**Common name:** NuGreen 2 Laminated raw particle board

**Grade:** M2

**Synonym:** Particle

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Classification:**

**None**

**Very important:** This product is not dangerous in the form in which it is sent by the manufacturer, but can become dangerous by downstream activities (for example, grinding, sanding, cutting, spraying) which reduce its particle size.

**Signal word:** None

**Hazard statements:**

None

**Precautionary statements:**

None

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	80 - 90
Melamine-Urea-Formaldehyde	N/A	7 - 10

---

### Section 4. First aid measures

**Description of first aid if required:**

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

**Eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes.

**Skin contact:**

Wash with plenty of water and soap.

**Inhalation:**

Bring the conscious victim to fresh air.

**Ingestion:**

Do NOT induce vomiting.

**Indication of immediate medical attention and special treatment needed, if necessary:**

Treat symptomatically

**Most important acute symptoms and effects:**

No known acute effects and/or symptoms.

**Most important delayed symptoms and effects:**

No known chronic effects and/or symptoms.

---

**Section 5. Firefighting measures****Flammability of the product:**

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

**Flash point:**

N/A

**Auto-ignition temperature:**

218°C / 424°F - 246°C / 475°F (variable)

**Products of combustion:**

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

**Special protective actions for fire-fighters:**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media:**

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

**Specific hazard arising from the chemical:**

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

---

**Section 6. Accidental release measures**

Product poses no accidental spill hazards.

**Personal precautions, protective equipment and emergency procedures:**

**For non emergency personnel:** Evacuate the area.

**For emergency personnel:** Wear appropriate protective equipment (see section 8)

**Environmental precautions:**

Not applicable

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

---

**Section 7. Handling and storage****Precautions in Handling:**

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values at which the product will be used.

---

**Section 8. Exposure Controls, Personal Protections**
**Control parameters:**

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Formaldehyde	50-00-0	Ceiling	3 mg/m <sup>3</sup>	CNESST
		STEL	2 ppm	OSHA
		TWA	0.75 ppm	OSHA
		Ceiling	0.3 ppm	ACGIH

**Engineering controls:**

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

**Personal protective equipment:**

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

**Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

## Section 10. Stability and reactivity

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

## Section 11. Toxicological information

### Acute toxicity:

Component	CAS	Value
Formaldehyde	50-00-0	CL <sub>50</sub> Inhalation: Rat - = 177 ppm 4h

### Skin corrosion/irritation:

Formaldehyde: May cause skin irritation

### Serious eye damage/irritation:

Formaldehyde: Causes serious eye irritation

### Respiratory or skin sensitisation:

Not applicable

### Gem cell mutagenicity:

Formaldehyde: Suspected of causing genetic defects

### Carcinogenicity:

Formaldehyde: May cause cancer

### Reproductive toxicity:

Not applicable

### STOT- Single exposure:

Formaldehyde: May cause respiratory irritation

### STOT- repeated exposure:

Not applicable

### Aspiration hazard:

Not applicable

### Information on likely route of exposure:

Not applicable

---

## Section 12. Ecological information

### Ecological data for aquatic environments:

None

### Persistence and degradability:

Data not available

### Bioaccumulative potential:

Data not available

### Mobility in soil:

Data not available

### Other adverse effects:

Data not available

---

---

## Section 13. Disposal considerations

### Waste disposal:

Dispose of the chemical waste in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

## Section 14. Transportation information

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### NFPA Classification:



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

### Date of issue:

2020-05-01

### Version:

2.0

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*

## NuGreen 2 Raw particle board

---

### Section 1. Identification

**Common name:** NuGreen 2 Raw particle board

**Grade:** M2

**Synonym:** Particle

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Classification:**

**None**

**Very important:** This product is not dangerous in the form in which it is sent by the manufacturer, but can become dangerous by downstream activities (for example, grinding, sanding, cutting, spraying) which reduce its particle size.

**Signal word:** None

**Hazard statements:**

None

**Precautionary statements:**

None

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	80 - 90
Melamine-Urea-Formaldehyde	N/A	7 - 10

---

### Section 4. First aid measures

**Description of first aid if required:**

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

**Eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes.

**Skin contact:**

Wash with plenty of water and soap.

**Inhalation:**

Bring the conscious victim to fresh air.

**Ingestion:**

Do NOT induce vomiting.

**Indication of immediate medical attention and special treatment needed, if necessary:**

Treat symptomatically

**Most important acute symptoms and effects:**

No known acute effects and/or symptoms.

**Most important delayed symptoms and effects:**

No known chronic effects and/or symptoms.

---

**Section 5. Firefighting measures****Flammability of the product:**

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

**Flash point:**

N/A

**Auto-ignition temperature:**

218°C / 424°F - 246°C / 475°F (variable)

**Products of combustion:**

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

**Special protective actions for fire-fighters:**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media:**

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

**Specific hazard arising from the chemical:**

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

---

**Section 6. Accidental release measures**

Product poses no accidental spill hazards.

**Personal precautions, protective equipment and emergency procedures:**

**For non emergency personnel:** Evacuate the area.

**For emergency personnel:** Wear appropriate protective equipment (see section 8)

**Environmental precautions:**

Not applicable

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

---

**Section 7. Handling and storage****Precautions in Handling:**

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values ??at which the product will be used.

---

**Section 8. Exposure Controls, Personal Protections**
**Control parameters:**

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Formaldehyde	50-00-0	Ceiling	3 mg/m <sup>3</sup>	CNESST
		STEL	2 ppm	OSHA
		TWA	0.75 ppm	OSHA
		Ceiling	0.3 ppm	ACGIH

**Engineering controls:**

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

**Personal protective equipment:**

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

**Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available



---

## Section 10. Stability and reactivity

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

## Section 11. Toxicological information

### Acute toxicity:

Component	CAS	Value
Formaldehyde	50-00-0	CL <sub>50</sub> Inhalation: Rat - = 177 ppm 4h

### Skin corrosion/irritation:

Formaldehyde: May cause skin irritation

### Serious eye damage/irritation:

Formaldehyde: Causes serious eye irritation

### Respiratory or skin sensitisation:

Not applicable

### Gem cell mutagenicity:

Formaldehyde: Suspected of causing genetic defects

### Carcinogenicity:

Formaldehyde: May cause cancer

### Reproductive toxicity:

Not applicable

### STOT- Single exposure:

Formaldehyde: May cause respiratory irritation

### STOT- repeated exposure:

Not applicable

### Aspiration hazard:

Not applicable

### Information on likely route of exposure:

Not applicable

---

## Section 12. Ecological information

### Ecological data for aquatic environments:

None

### Persistence and degradability:

Data not available

### Bioaccumulative potential:

Data not available

### Mobility in soil:

Data not available

### Other adverse effects:

Data not available

---

---

## Section 13. Disposal considerations

### Waste disposal:

Dispose of the chemical waste in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

## Section 14. Transportation information

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### NFPA Classification:



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

### Date of issue:

2020-05-01

### Version:

2.0

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*

## NuGreen MDF laminated

---

### Section 1. Identification

**Common name:** NuGreen MDF laminated

**Grade:** NuGreen MR50, NuGreen 0

**Synonym:** MDF panels

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**


---

### Section 2. Hazards identifications

**Very important: This product is not dangerous in the form in which it is shipped by the manufacturer, but can become dangerous through downstream activities (for example, grinding, sanding, cutting, spraying) that reduce its particle size. These hazards are described below.**

The classifications below are based on wood dust and the polymer component.

**Classification:**



Combustible dust

Respiratory sensitization, Category 1

Skin sensitization, Category 1

Carcinogenicity, Category 2

Specific target organ toxicity - Repeated exposure, Category 2

**Signal word:** Danger

**Hazard statements:**

H317: May cause an allergic skin reaction.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351: Suspected of causing cancer.

H373: May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements:**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: Wear respiratory protection.

P302+P352: IF ON SKIN: Wash with plenty of water and soap.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P314: Get medical advice/attention if you feel unwell.

P321: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

P333+P313: If skin irritation or a rash occurs: Get medical advice/attention.

P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

P501: Dispose of contents / container by a local waste disposal company according to regional regulations.

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	85 - 94
Methylene diphenyl 4,4'-diisocyanate	101-68-8	2 - 5
Paraffin waxes	64742-61-6	0.7 - 1.2
Urea	57-13-6	0.3 - 0.8

---

### Section 4. First aid measures

#### Description of first aid if required:

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

#### Eye contact:

Rinse eyes thoroughly with water for at least 15 minutes.

#### Skin contact:

Wash with plenty of water and soap.

#### Inhalation:

Bring the conscious victim to fresh air.

#### Ingestion:

Do NOT induce vomiting.

#### Indication of immediate medical attention and special treatment needed, if necessary:

Treat symptomatically

#### Most important acute symptoms and effects:

No known acute effects and/or symptoms.

#### Most important delayed symptoms and effects:

May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

---

### Section 5. Firefighting measures

#### Flammability of the product:

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

#### Flash point:

N/A

**Auto-ignition temperature:**

218°C / 424°F - 246°C / 475°F (variable)

**Products of combustion:**

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

**Special protective actions for fire-fighters:**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media:**

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

**Specific hazard arising from the chemical:**

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

**Section 6. Accidental release measures**

Product poses no accidental spill hazards.

**Personal precautions, protective equipment and emergency procedures:****For non emergency personnel:** Evacuate the area.**For emergency personnel:** Wear appropriate protective equipment (see section 8)**Environmental precautions:**

Not applicable

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

**Section 7. Handling and storage****Precautions in Handling:**

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values at which the product will be used.

**Section 8. Exposure Controls, Personal Protections****Control parameters:**

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Methylene diphenyl 4,4'-diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
Paraffin waxes	64742-61-6	TWA	2 mg/m <sup>3</sup>	CNESST
		TWA	2 mg/m <sup>3</sup>	ACGIH

**Engineering controls:**

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

**Personal protective equipment:**

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

**Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

**Section 10. Stability and reactivity**

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

**Section 11. Toxicological information****Acute toxicity:**

Component	CAS	Value
Methylene diphenyl 4,4'-diisocyanate	101-68-8	DL <sub>50</sub> Oral: Rat = 9200 mg/kg CL <sub>50</sub> Inhalation: Rat = 2.24 mg/L 1h
Paraffin waxes	64742-61-6	DL <sub>50</sub> Oral: Rat > 5000 mg/kg DL <sub>50</sub> Cutaneous: Rabbit = 4000 mg/kg
Urea	57-13-6	DL <sub>50</sub> Oral: Rat = 8471 mg/kg DL <sub>50</sub> Oral: Mouse = 11000 mg/kg

**Skin corrosion/irritation:**

Methylene diphenyl 4,4'-diisocyanate: Causes skin irritation

**Serious eye damage/irritation:**

Methylene diphenyl 4,4'-diisocyanate: Causes serious eye irritation

**Respiratory or skin sensitisation:**

Methylene diphenyl 4,4'-diisocyanate: May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled

**Gem cell mutagenicity:**

Not applicable

**Carcinogenicity:**

Methylene diphenyl 4,4'-diisocyanate: Suspected of causing cancer

**Reproductive toxicity:**

Not applicable

**STOT- Single exposure:**

Methylene diphenyl 4,4'-diisocyanate: May cause respiratory irritation

**STOT- repeated exposure:**

Methylene diphenyl 4,4'-diisocyanate: May cause damage to organs through prolonged or repeated exposure (respiratory system)

**Aspiration hazard:**

Not applicable

**Information on likely route of exposure:**

Not applicable

---

**Section 12. Ecological information****Ecological data for aquatic environments:**

Component	CAS	Value
Methylene diphenyl 4,4'-diisocyanate	101-68-8	CE <sub>50</sub> - Daphnia magna 0.35 mg/L - 24h
Urea	57-13-6	CL <sub>50</sub> - Poecilia reticulata (guppy) 17500 mg/L - 96h CE <sub>50</sub> - Daphnia magna 3910 mg/L - 48h

**Persistence and degradability:**

Data not available

**Bioaccumulative potential:**

Data not available

**Mobility in soil:**

Data not available

**Other adverse effects:**

Data not available

---

**Section 13. Disposal considerations****Waste disposal:**

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

## Section 14. Transportation information

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### NFPA Classification:



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

### Date of issue:

2020-05-13

### Version:

2.1

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*



## Raw particle board

---

### Section 1. Identification

**Common name:** Raw particle board

**Grade:** M0, M1, MS, M2, M3i, LD1, LD2

**Synonym:** Particle

**Material uses:** Furniture, cabinets, finishing

**Supplier / Manufacturer:**

**Uniboard Canada Inc.**

5555 Rue Ernest-Cormier

Laval

Québec, Canada, H7C2S9

Phone: 450-664-6000

**In case of emergency:**

**450-664-6000**

---

### Section 2. Hazards identifications

**Classification:**

**None**

**Very important:** This product is not dangerous in the form in which it is sent by the manufacturer, but can become dangerous by downstream activities (for example, grinding, sanding, cutting, spraying) which reduce its particle size.

**Signal word:** None

**Hazard statements:**

None

**Precautionary statements:**

None

---

### Section 3. Composition and information on ingredients

Name	CAS	Concentration %
Wood (woody fibres)	N/A	80 - 90
Melamine-Urea-Formaldehyde	N/A	7 - 10

---

### Section 4. First aid measures

**Description of first aid if required:**

In solid form, classification, health hazards and first aid measures are most unlikely. In case of fine particles and dust from secondary transformation exposure, apply the following:

**Eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes.

**Skin contact:**

Wash with plenty of water and soap.

**Inhalation:**

Bring the conscious victim to fresh air.

**Ingestion:**

Do NOT induce vomiting.

**Indication of immediate medical attention and special treatment needed, if necessary:**

Treat symptomatically

**Most important acute symptoms and effects:**

No known acute effects and/or symptoms.

**Most important delayed symptoms and effects:**

No known chronic effects and/or symptoms.

---

**Section 5. Firefighting measures****Flammability of the product:**

The product is combustible. Wood dust can form an explosive mixture with air under the right circumstances and at the right concentrations.

**Flash point:**

N/A

**Auto-ignition temperature:**

218°C / 424°F - 246°C / 475°F (variable)

**Products of combustion:**

Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

**Special protective actions for fire-fighters:**

Wear self-contained breathing apparatus and appropriate protective clothing.

**Suitable extinguishing media:**

Water spray, Carbon dioxide, Dry Chemical, Dry sand.

**Specific hazard arising from the chemical:**

Product base is wood fibres. Product is combustible. It will burn if involved in a fire. Wood dusts may form an explosive mix with air in the right circumstances and concentrations.

---

**Section 6. Accidental release measures**

Product poses no accidental spill hazards.

**Personal precautions, protective equipment and emergency procedures:**

**For non emergency personnel:** Evacuate the area.

**For emergency personnel:** Wear appropriate protective equipment (see section 8)

**Environmental precautions:**

Not applicable

**Methods and material for containment and cleaning up:**

Use appropriate tools to put the spilled solid in a convenient waste disposal container. Broom and vacuum cleaner for dust.

---

**Section 7. Handling and storage****Precautions in Handling:**

Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

**Precautions in Storage:**

Keep container tightly closed in a cool and well-ventilated place. It must be stored in a place where the ambient temperature and humidity are close to the values ??at which the product will be used.

---

**Section 8. Exposure Controls, Personal Protections**
**Control parameters:**

Component	CAS	Value	Control parameters	Basis
Wood (woody fibres)	N/A	TWA	5.0 mg/m <sup>3</sup>	Québec RQMT
		TWA	15.0 mg/m <sup>3</sup>	OSHA
		TWA	5.0 mg/m <sup>3</sup> (inhalable fraction)	OSHA
Formaldehyde	50-00-0	Ceiling	3 mg/m <sup>3</sup>	CNESST
		STEL	2 ppm	OSHA
		TWA	0.75 ppm	OSHA
		Ceiling	0.3 ppm	ACGIH

**Engineering controls:**

Ensure adequate ventilation and a good air outlet in order to keep contaminant concentrations below the permitted exposure limits. It is essential to consider the nature and the dangerousness (explosiveness) of wood dust in the process of selecting control systems.

**Personal protective equipment:**

**Eyes:** Wear safety glasses with side shields.

**Skin/body:** Wear standard work clothes to prevent abrasion.

**Respiratory:** If ventilation is insufficient, choose appropriate respiratory protection according to levels and duration of exposure.

**Hands:** Wear work gloves to avoid cuts, splinters or abrasions.

**Other:** An emergency eye and body wash must be available on site.

---

**Section 9. Physical and chemical properties**

**Physical state:** Solid

**Color:** Variable

**Odour:** Wood

**Melting point/Freezing point:** Data not available

**Boiling point:** Data not available

**Appearance:** Panels

**Flash point:** Data not available

**Auto-ignition temperature:** 218°C / 424.4°F - 246°C / 475°F (variable)

**pH:** Data not available

**Solubility:** Insoluble

**Density:** Data not available

---

## Section 10. Stability and reactivity

**Chemical reactivity:** Stable under recommended storage conditions.

**Conditions to avoid:** Open flames, high temperatures, excessive humidity

**Incompatible materials:** Oxidizing agents, strong acids, strong bases

**Hazardous decomposition products:** Carbon oxides, nitrogen oxides, aldehydes, ketones, organic acids, alcohols

---

## Section 11. Toxicological information

### Acute toxicity:

Component	CAS	Value
Formaldehyde	50-00-0	CL <sub>50</sub> Inhalation: Rat - = 177 ppm 4h

### Skin corrosion/irritation:

Formaldehyde: May cause skin irritation

### Serious eye damage/irritation:

Formaldehyde: Causes serious eye irritation

### Respiratory or skin sensitisation:

Not applicable

### Gem cell mutagenicity:

Formaldehyde: Suspected of causing genetic defects

### Carcinogenicity:

Formaldehyde: May cause cancer

### Reproductive toxicity:

Not applicable

### STOT- Single exposure:

Formaldehyde: May cause respiratory irritation

### STOT- repeated exposure:

Not applicable

### Aspiration hazard:

Not applicable

### Information on likely route of exposure:

Not applicable

---

## Section 12. Ecological information

### Ecological data for aquatic environments:

None

### Persistence and degradability:

Data not available

### Bioaccumulative potential:

Data not available

### Mobility in soil:

Data not available

### Other adverse effects:

Data not available

---

---

## Section 13. Disposal considerations

### Waste disposal:

Dispose of the chemical waste is in conformity with the federal, provincial and local laws. Store the residues of the product in safe containers.

---

## Section 14. Transportation information

No TDG/DOT/IMDG/IATA Classification

---

## Section 15. Regulatory information

### NFPA Classification:



Health: 0  
Flammable: 0  
Reactivity: 0  
Specials conditions: 0

**Legend: 4: Severe, 3: High, 2: Moderate, 1: Slightly, 0: Not hazardous**

### U.S. Federal regulations

**California proposition 65 requirements:** Piercing, sawing, sanding or shaping wood products creates wood dusts, a substance recognized for causing cancer according to the state of California. Avoid inhaling wood dusts or use a dust mask or other personal protection measures.

---

## Section 16. Additional information

### Date of issue:

2020-05-13

### Version:

2.1

### Elaborated by:

Toxyscan inc.

### Notice to reader:

To the best of our knowledge, the information contained herein is accurate. However, neither Toxyscan inc., nor the supplier, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

### Références:

- *Répertoire toxicologique of la Commission des normes, de l'équité, de la santé et de la sécurité du travail.*
- *Registry of Toxic effects of Chemical Substances of the Canadian Centre for Occupational Health and Safety.*
- *Material safety data sheet from the manufacturer.*
- *Hazardous Products Regulations (DORS/2015-17).*
- *Canadian Transport of Dangerous Goods.*
- *GHS (rev.8) (2019) globally harmonized system of classification and labeling of chemicals - United Nations*